



## Mobil Super 2000 X2 10W-40

### Premium Semi-Synthetic Passenger Vehicle Engine Oil

#### Product Description

The Mobil Super 2000 range of lubricants are enhanced-premium semi-synthetic engine oils, designed to provide an excellent level of protection and performance

#### Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 2000 X2 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection

#### Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Stop and Go City Driving
- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

#### Specifications and Approvals

<b>Mobil Super 2000 X2 meets or exceeds the requirements of:</b>	<b>10W-40</b>
API	SN/SM/SL
ACEA	A3/B3

<b>Mobil Super 2000 X2 has the following builder approvals:</b>	<b>10W-40</b>
VW	505.00 /501.01
MB-Approval	229.1

<b>Mobil Super 2000 X2 is recommended by ExxonMobil for use in applications requiring:</b>	<b>10W-40</b>
--	---------------

## Typical Properties

### Mobil Super 2000 X2

SAE Grade	10W-40
Viscosity, ASTM D 445	
cSt @ 40°C	92
cSt @ 100°C	14.4
Viscosity Index, ASTM D 2270	154
Sulfated Ash, wt%, ASTM D 874	0.97
HTHS Viscosity., mPa*s @ 150°C, ASTM D4683	4.0
Pour Point, °C, ASTM D 97	-36
Flash Point, °C, ASTM D 92	220
Density @ 15 °C, kg/l, ASTM D4052	0.869

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

5-2015

ExxonMobil Asia Pacific Ltd  
1 HarbourFront Place  
#06-00 HarbourFront Tower One  
Singapore 098633

+65 6885 8000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.